LUSCOMBE AIRPLANE CORPORATION

MODELS: Luscombe Phantom 1 and 1S

T.C. NUMBER: ATC 552

I - SPECIFICATIONS PERTINENT TO BOTH MODELS

Engine Placard limits	Warner Super Scarab Series 50 Maximum, except take-off in. Hg., 2050 rpm (145 hp)			
	Take-off (one minute)	143 11	Pi	
	in. Hg., 2050 rpm (145 b	la.	
Propeller	Maximum permissible diame	eter	89 in.	
Fuel capacity	33 gallons (two tanks, or	ne 16	-1/2 gallo	n tank in
. doz oupudzoj	each wing) (+23)		-	
Oil capacity	3-1/2 gallons (-5)			
No. passengers	1 (+25)			
Spec. basis	Approved Type Certificate	e No.	552	
Serial Nos.	101 and up manufactured	p rior	to 7/7/41	eligible.
	Approval expired as of	that	date.	
EQUIPMENT: (Datum is wing leading edge) (* Means net increase)				
Class I:				
A. Landplane				
101. Propeller - adj	i. metal	62	lbs.	(-38)
102. Engine ring cov	v1	25	lbs.	(-23)
103. 21 in. streamline wheels (Autofan)				•
with brakes and 4-ply tires				(+6)
104. Tail wheel (4-1/2 in. diameter with				
solid tire)		6	lbs.	(+182)
·				
B. Seaplane: Items 101 and 102 PLUS				
151. Battery (just a	ift of firewall)		lbs.	(- 5)
152. Starter (Eclips	Be Y-150)		lbs.	(-12) (-15)
153. Generator (Boso	en)	10	IDS.	(-15)
	154. Edo 44-2425 floats			
155. Auxiliary fin				
Class II:				
A. Landplane:				
200. Miscellaneous	items as noted in			
approved weight	t and balance report.			
-				
B. Seaplane: Item 200	PLUS			
251. Propeller - fix		****		E 15-
(Curtiss 55511)		Net	decrease 1	12 TDR.
Class III:				
A. Iandplane: Items 15	1, 152, 153, 251 PLUS			
301. Radio (RCA AVR	7 series)	20	lbs.	(+68)
302. Landing lights	,		lbs.	• • •
303. Additional inst			lbs.	
304. 8 in. streamlin				(+182)
305. Bonding and sh				
•				

306. 6.50-10 wheels with brakes 307. Tail wheel lock

Net decrease 4 lbs. (+6)

B. Seaplane: Items 302, 303 and 305 PLUS 351. Battery (just aft of firewall)

10 lbs.* (-5)

NOTE 1. All airplanes of the seaplane type (Model 1S) must have approved wing spoilers approximately 36 inches long installed on the leading edges of both wings. The inboard ends of the spoilers are attached to the first wing ribs inboard of front wing strut attachment fittings (approximately 5 inches inboard of the strut points).

NOTE 2. Landplane baggage may be increased to 112 lbs. when substantiated by actual weight and balance report. This necessitates recheck of C.G. limits for any future change in equipment.

NOTE 3. Eligible for export to all countries except Great Britain, Canada, Australia and New Zealand (July 7, 1941).

II - Model Phantom 1, Designation 2 PCLM

Level flight or climb - 160 mph True Ind. Glide or dive - 240 mph True Ind. Flaps extended - 149 mph True Ind. Placard speeds Baggage 66 lbs. (+48) (See NOTE 2)

Standard weight 1950 lbs. C.G. limits (+15.25) and (+18.9)

III - Model Phantom 1S, Designation 2 PCaM

Placard speeds

Level flight or climb - 150 mph True Ind. Glide or dive - 200 mph True Ind. Flaps extended - 149 mph True Ind.

32 lbs. (+48) Paggage

Standard weight 2180 lbs.

C.G. limits (+18.2) and (+19.6)